



Figure 4. Comparisons across models. From Top to Bottom: PYdist, PYall, gPb, FH, MS, Ncuts

- [5] D. Comaniciu and P. Meer. Mean shift: A robust approach toward feature space analysis. *PAMI*, 24(5):603–619, May 2002.
- [6] D. Cremers, M. Rousson, and R. Deriche. A review of statistical approaches to level set segmentation: Integrating color, texture, motion and shape. *IJCV*, 72(2):195–215, 2007.
- [7] P. F. Felzenszwalb and D. P. Huttenlocher. Efficient graph-based image segmentation. *IJCV*, 59(2):167–181, 2004.
- [8] S. Geman and D. Geman. Stochastic relaxation, Gibbs distributions, and the Bayesian restoration of images. *PAMI*, 6(6):721–741, 1984.
- [9] D. Hoiem, A. A. Efros, and M. Hebert. Geometric context from a single image. In *ICCV*, volume 1, pages 654 – 661, 2005.
- [10] J. Lafferty, A. McCallum, and F. Pereira. Conditional random fields: Probabilistic models for segmenting and labeling sequence data. In *ICML*, pages 282–289, 2001.
- [11] T. Malisiewicz and A. A. Efros. Improving spatial support for objects via multiple segmentations. In *BMVC*, September 2007.
- [12] D. Martin, C. Fowlkes, D. Tal, and J. Malik. A database of human segmented natural images and its application to evaluating segmentation algorithms and measuring ecological statistics. In *ICCV*, volume 2, pages 416–423, July 2001.
- [13] D. R. Martin, C. C. Fowlkes, and J. Malik. Learning to detect natural image boundaries using local brightness, color, and texture cues. *PAMI*, 26:530–549, May 2004.
- [14] T. P. Minka. Expectation propagation for approximate bayesian inference. In *UAI*, pages 362–369, 2001.
- [15] R. Nock and F. Nielsen. Statistical region merging. *PAMI*, 26:1452–1458, November 2004.
- [16] A. Oliva and A. Torralba. Modeling the shape of the scene: A holistic representation of the spatial envelope. *IJCV*, 42(3):145–175, 2001.
- [17] J. Pitman and M. Yor. The two-parameter Poisson–Dirichlet distribution derived from a stable subordinator. *Annals of Probability*, 25(2):855–900, 1997.
- [18] W. M. Rand. Objective criteria for the evaluation of clustering methods. *JASA*, 66:846–850, 1971.
- [19] X. Ren and J. Malik. A probabilistic multi-scale model for contour completion based on image statistics. In *ECCV*, volume 1, pages 312–327, 2002.
- [20] X. Ren and J. Malik. Learning a classification model for segmentation. In *ICCV*, volume 1, pages 10–17, 2003.
- [21] B. C. Russell, A. A. Efros, J. Sivic, W. T. Freeman, and A. Zisserman. Using multiple segmentations to discover objects and their extent in image collections. In *CVPR*, pages 1605–1614, 2006.
- [22] G. Sfikas, C. Nikou, and N. Galatsanos. Edge preserving spatially varying mixtures for image segmentation. *CVPR*, 0:1–7, 2008.
- [23] J. Shi and J. Malik. Normalized cuts and image segmentation. *PAMI*, 22(8), 2000.
- [24] A. Shyr, T. Darrell, M. I. Jordan, and R. Urtasun. Supervised hierarchical Pitman-Yor process for natural scene segmentation. In *CVPR*, pages 2281–2288, 2011.
- [25] E. B. Sudderth and M. I. Jordan. Shared segmentation of natural scenes using dependent Pitman-Yor processes. In *NIPS*, pages 1585–1592, 2008.
- [26] D. Sun, E. B. Sudderth, and M. Black. Layered image motion with explicit occlusions, temporal consistency, and depth ordering. In *NIPS*, pages 2226–2234, 2010.
- [27] Z. Tu and S. Zhu. Image segmentation by data-driven Markov Chain Monte Carlo. *PAMI*, 24:657–673, 2002.
- [28] J. Y. A. Wang and E. H. Adelson. Representing moving images with layers. *IEEE Tran. IP*, 3(5):625–638, Sept. 1994.
- [29] M. Welling and K. Kurihara. Bayesian K-means as a “Maximization-Expectation” algorithm. In *SDM*, 2006.