

References

- [1] M. Attene, S. Katz, M. Mortara, G. Patane, M. Spagnuolo, and A. Tal. Mesh segmentation — A comparative study. In *SMI*, 2006.
- [2] Xiaobai Chen, Aleksey Golovinskiy, and Thomas Funkhouser. A benchmark for 3D mesh segmentation. *ACM Transactions on Graphics (Proc. SIGGRAPH)*, 28(3):73:1–73:12, 2009.
- [3] Evangelos Kalogerakis, Aaron Hertzmann, and Karan Singh. Learning 3D Mesh Segmentation and Labeling. *ACM Transactions on Graphics*, 29(4):102:1–102:12, July 2010.
- [4] David M. Blei and Peter I. Frazier. Distance dependent Chinese restaurant processes. *J. Mach. Learn. Res.*, 12:2461–2488, November 2011.
- [5] S. Ghosh, A. B. Ungureanu, E. B. Sudderth, and D. Blei. Spatial distance dependent Chinese restaurant processes for image segmentation. In *NIPS*, pages 1476–1484, 2011.
- [6] D. Hirshberg, M. Loper, E. Rachlin, and M.J. Black. Coregistration: Simultaneous alignment and modeling of articulated 3D shape. In *ECCV*, pages 242–255, 2012.
- [7] R. M. Neal. Markov chain sampling methods for Dirichlet process mixture models. *JCGS*, 9(2):249–265, 2000.
- [8] D. Anguelov, D. Koller, H. Pang, P. Srinivasan, and S. Thrun. Recovering articulated object models from 3d range data. In *UAI*, pages 18–26, 2004.
- [9] J. Franco and E. Boyer. Learning temporally consistent rigidities. In *IEEE CVPR*, pages 1241–1248, 2011.
- [10] E. B. Fox. *Bayesian Nonparametric Learning of Complex Dynamical Phenomena*. PhD thesis, Massachusetts Institute of Technology, Cambridge, MA, 2009.
- [11] A. K. Gupta and D. K. Nagar. *Matrix Variate Distributions*. Chapman & Hall/CRC, October 2000.
- [12] Tong-Yee Lee, Yu-Shuen Wang, and Tai-Guang Chen. Segmenting a deforming mesh into near-rigid components. *The Visual Computer*, 22(9):729–739, September 2006.
- [13] Guy Rosman, Michael M. Bronstein, Alexander M. Bronstein, Alon Wolf, and Ron Kimmel. Group-valued regularization framework for motion segmentation of dynamic non-rigid shapes. In *SSVM’11*, pages 725–736, 2012.
- [14] Stefanie Wuhler and Alan Brunton. Segmenting animated objects into near-rigid components. *The Visual Computer*, 26:147–155, 2010.
- [15] N. Hasler, C. Stoll, M. Sunkel, B. Rosenhahn, and H.-P. Seidel. A statistical model of human pose and body shape. In *Computer Graphics Forum (Proc. Eurographics 2009)*, volume 2, pages 337–346, March 2009.
- [16] R. N. Shepard. Multidimensional scaling, tree-fitting, and clustering. *Science*, 210:390–398, October 1980.
- [17] Wen-Yen Chen, Yangqiu Song, Hongjie Bai, Chih-Jen Lin, and Edward Y. Chang. Parallel spectral clustering in distributed systems. *IEEE PAMI*, 33(3):568–586, 2011.
- [18] Rong Liu and Hao Zhang. Segmentation of 3D meshes through spectral clustering. In *Pacific Conference on Computer Graphics and Applications*, pages 298–305, 2004.
- [19] Edilson de Aguiar, Christian Theobalt, Sebastian Thrun, and Hans-Peter Seidel. Automatic conversion of mesh animations into skeleton-based animations. *Computer Graphics Forum*, 27(2):389–397, 2008.
- [20] Alexander Bronstein, Michael Bronstein, and Ron Kimmel. Calculus of nonrigid surfaces for geometry and texture manipulation. *IEEE Tran. on Viz. and Computer Graphics*, 13:902–913, 2007.
- [21] Oren Freifeld and Michael J. Black. Lie bodies: A manifold representation of 3D human shape. In *European Conf. on Computer Vision (ECCV)*, Part I, LNCS 7572, pages 1–14. Springer-Verlag, October 2012.