

3.19	Comparison of <i>sparse</i> ₅₀ graph with graphs generated using the BKM, CONF, and CA models with $\rho = 0.048$	89
3.20	Clustering coefficient distribution for <i>moderate</i> ₅₀ graph and corresponding graphs generated by the SC model. Vertices with degree less than 2 are ignored.	93
3.21	Vertex degree vs clustering coefficient correlation plot for <i>moderate</i> ₅₀ graph and corresponding graphs generated by the SC model.	94
3.22	Number of people infected on each day of an SIR simulation with low transmissibility $\rho = .0122$ for the <i>moderate</i> ₅₀ graph and the Spatial-Clustering (SC), Configuration (CONF), and Configuration with Assortativity (CA) models. <i>x</i> -axis represents the timestep for the simulation (days). <i>y</i> -axis gives the number of people in the “infected” state during that timestep. .	95
3.23	Number of people infected on each day of an SIR simulation with low transmissibility $\rho = .122$ for the <i>moderate</i> ₅₀ graph and the Spatial-Clustering (SC), Configuration (CONF), and Configuration with Assortativity (CA) models. <i>x</i> -axis represents the timestep for the simulation (days). <i>y</i> -axis gives the number of people in the “infected” state during that timestep. .	96
4.1	Simple graph of two vertices between two components of equal size. Vaccinating <i>b</i> alone gives really no improvement but vaccinating <i>b</i> along with <i>a</i> gives a major improvement by separating halves of the graph. For the <i>budgeted maximization problem</i> this demonstrates the objective function <i>f</i> violates the submodular property of “diminishing returns.”	102
4.2	Instance of BV for which sum-of-squares partition problem is a poor proxy. 104	
4.3	Comparison of experimental runs on the <i>moderate</i> ₁ HCW contact networks for the greedy budgeted vertex cover algorithm and an upper bound calculated by solving the LP relaxation. The x-axis is truncates values that have the same y values.	109
4.4	Example graph showing that h_G+ is not submodular.	111
4.5	Bad Case for BMD. Suppose that $B = X - 1$ and $X = \frac{N}{3}$ so that each gray vertex has degree $\frac{2N}{3}$ and each black vertex has degree $\frac{N}{3}$. The optimal solution would be <i>B</i> black vertices resulting in reducing the maximum degree to $\frac{N}{3} + 1$. A greedy solution based on degree would pick <i>B</i> of the gray and the maximum degree would remain $\frac{2N}{3}$. The greedy algorithm is thus <i>at least</i> a 2 approximation.	112